



## SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDrive Sport2, 75Nm, powered by Yamaha
<b>BEDIENINGSUNIT</b>	RideControl Dash
<b>DISPLAY</b>	RideControl Dash, full color lcd screen
<b>ACCU</b>	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible (exclude XS size)
FRAME	
<b>MATEN</b>	XS, S, M, L
<b>FRAME</b>	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
<b>VOORVORK</b>	SR Suntour XCM34, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
<b>DEMPER</b>	n/a
ONDERDELEN	
<b>STUUR</b>	Giant Connect Riser 31.8x620mm (XS/S), 690mm(M/L)
<b>HANDVATTEN</b>	Liv Contact Ergo Max Plus
<b>STUURPEN</b>	Giant Contact (XS/S/M: 80mm, L:100mm)
<b>ZADELPEN</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>ZADEL</b>	Liv Sport Comfort
<b>PEDALEN</b>	Aluminum Platform
AFMONTAGE	
<b>SHIFTERS</b>	Shimano Altus
<b>VOORDERAILLEUR</b>	n/a
<b>ACHTERDERAILLEUR</b>	Shimano Alivio, 9-speed
<b>REMMEN</b>	Tektro HD-M276, hydraulic disc, 180mm
<b>REMHENDELS</b>	Tektro HD-M276
<b>CASSETTE</b>	Shimano CS-HG200, 11-36T, 9-speed
<b>KETTING</b>	KMC e.9 Sport, e-bike optimized
<b>CRANKSET</b>	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
<b>BOTTOM BRACKET</b>	n/a

WIELSET	
<b>VELGEN</b>	eX25, Tubeless Ready, 622x25 Aluminium
<b>NAVEN</b>	Giant eTracker, [F] 110x15 [R] 1142x12
<b>SPAKEN</b>	Stainless steel
<b>BANDEN</b>	Crosscut Gravel 2, 700x57, Wire Bead, Tubeless Ready
ACCESSOIRES	
<b>VERLICHTING</b>	Recon E HL50 StVZO [F]AXA NYX 6-12V E-bike tail light [R]
<b>SLOT</b>	ABUS Xplus battery lock
<b>DRAGER</b>	MIK rack. System bag & basket compatible

**Adviesprijs: € 3.399,00**

## GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	380	410	435	490
Zitbuis Hoek	75,0°	74,5°	73,5°	73,0°
Frame Lengte (horizontaal) (mm)	575	585	605	620
Balhoofdbuis Lengte (mm)	135	145	160	175
Balhoofdbuis Hoek	69,0°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Naloop (mm)	88	84	84	84
Wielbasis (mm)	1149	1148	1157	1166
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	660	672	686	700
Reach (mm)	398	398	401	406
Stand Over Height (mm)	676	684	663	676
Stuur breedte (mm)	650	650	690	690
Stuurpen Lengte (mm)	80	80	100	100
Cranklengte (mm)	165	165	170	170
Wielmaat	700C	700C	700C	700C

*Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.*