

ANYTOUR E+ 5 DD

GIANT

SPECIFICATIES

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|--|
| MOTOR | Giant SyncDrive Core, 55Nm, PedalPlus 6-sensor technology |
| BEDIENINGSUNIT | Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W) |
| DISPLAY | Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation |
| ACCU | Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production |
| FRAME | |
| MATEN | M, L, XL |
| KLEUREN | Charcoal / Black |
| FRAME | ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand |
| VOORVORK | SR Suntour NEX E25 700C Coil 63mm travel |
| DEMPER | n/a |
| ONDERDELEN | |
| STUUR | Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm |
| HANDVATTEN | Giant Comfort Ergo Microtech Plus Lock-on |
| STUURPEN | Giant Contour, EVO display integrated, adjustable |
| ZADELPEN | Suspension dropper post, handlebar operated remote control, 30.9mm |
| ZADEL | Selle Royal Look-In gel |
| PEDALEN | Aluminum, Wellgo C211DU, PP body, anti-slip |
| AFMONTAGE | |
| SHIFTERS | Shimano Nexus 7speed Revoshift |
| REMMEN | Tektro HD-M275, hydraulic disc, 180mm [F], 160mm [R] |
| REMHENDELS | Tektro HD-M275 |
| CASSETTE | Gates CDC stainless steel 22T rear sprocket |
| KETTING | Gates CDC Carbon Drive 120T CenterTrack belt |
| CRANKSET | Gates CDC CenterTrack 46T front sprocket |
| BOTTOM BRACKET | n/a |

| WIELSET | |
|--------------------|--|
| VELGEN | Giant Double Wall Aluminum 622x21 |
| NAVEN | Shimano HB-MT200 9mm QR Disc [F], Shimano Nexus 7 Disc brake [R] |
| SPAKEN | Stainless |
| BANDEN | Schwalbe Marathon 622x50 Green Guard |
| ACCESSOIRES | |
| VERLICHTING | Giant Recon HL50, 50 lux [F]AXA Juno 6-12V E-bike tail light [R] |
| SLOT | ABUS Xplus Battery Lock / Abus 5755L XPlus R (ART certified) |
| DRAGER | MIK HD rack. System bag & basket compatible |

Adviesprijs: € 3.599,00

GEOMETRIE

| FRAME | M | L | XL |
|---------------------------------|-------|-------|-------|
| Zitbuis Lengte (mm) | 460 | 480 | 550 |
| Zitbuis Hoek | 72,5° | 72,0° | 72,0° |
| Frame Lengte (horizontaal) (mm) | 590 | 610 | 630 |
| Balhoofdbuis Lengte (mm) | 170 | 170 | 170 |
| Balhoofdbuis Hoek | 69,5° | 69,5° | 69,5° |
| Vork Sprong (mm) | 44 | 44 | 44 |
| Naloop (mm) | 70 | 70 | 70 |
| Wielbasis (mm) | 1114 | 1128 | 1148 |
| Liggende achtervork lengte (mm) | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 91 | 91 | 91 |
| Stack (mm) | 663 | 663 | 663 |
| Reach (mm) | 381 | 394 | 414 |
| Stand Over Height (mm) | 818 | 816 | 855 |
| Stuur breedte (mm) | 680 | 680 | 680 |
| Stuurpen Lengte (mm) | 90 | 110 | 110 |
| Cranklengte (mm) | 170 | 170 | 170 |
| Wielmaat | 700C | 700C | 700C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.