



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Black
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Connect XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
HANDVATTEN	Velo cork tape with gel
STUURPEN	Giant Sport XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm
ZADELPEN	Giant D-Fuse, alloy, 14mm offset
ZADEL	Giant Approach
PEDALEN	platform pedal [GU,GV,GJ] pedal with toe clips/straps [rest of GSC]
AFMONTAGE	
SHIFTERS	Shimano Sora
VOORDERAILLEUR	Shimano Sora
ACHTERDERAILLEUR	Shimano Sora
REMMEN	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano Sora
CASSETTE	Shimano CS-HG400, 11x34
KETTING	KMC X9
CRANKSET	Shimano Sora, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant S-R2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	S-R3 AC all condition Road 700X32C (34mm)
EXTRA'S	fender mount, 38mm max tire size

Adviesprijs: € 1.199,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	465	500	535	555	585
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	535	550	565	580	595
Balhoofdbuis Lengte (mm)	135	150	170	190	215
Balhoofdbuis Hoek	71,8°	72,0°	72,5°	72,5°	72,5°
Vork Sprong (mm)	53	53	53	53	53
Naloop (mm)	61,3	59,6	56,4	56,4	56,4
Wielbasis (mm)	1003	1011	1015	1031	1046
Liggende achtervork lengte (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	559	574	595	614	638
Reach (mm)	375	380	383	392	400
Stand Over Height (mm)	759	783	810	829	856
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	100	110	110
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.