

# DEFY ADVANCED PRO 1

**GIANT**

## SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Meteor Storm
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SL D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
ZADELPEN	Giant D-Fuse SL, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
AFMONTAGE	
SHIFTERS	SRAM Rival eTap AXS
VOORDERAILLEUR	SRAM Rival eTap AXS
ACHTERDERAILLEUR	SRAM Rival eTap AXS
REMMEN	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
KETTING	SRAM Rival D1
CRANKSET	SRAM Rival D1 DUB, 33/46 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 36 Carbon Disc WheelSystem
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRA'S	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size

Adviesprijs: € 5.199,00

## GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	480	515	535	565
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	595
Balhoofdbuis Lengte (mm)	140	150	175	195	215
Balhoofdbuis Hoek	71,8°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	63,4	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	998	1010	1025	1040
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stand Over Height (mm)	733	762	796	814	841
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	100	110	110
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.