



## SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Metal/Shoreline
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	cork tape with gel
STUURPEN	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELLEN	Giant D-Fuse, alloy, 14mm offset
ZADEL	Giant Approach
AFMONTAGE	
SHIFTERS	Shimano GRX RX-400, 2x10
VOORDERAILEUR	Shimano Tiagra
ACHTERDERAILEUR	Shimano GRX RX-400
REMMEN	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-400 hydraulic
CASSETTE	Shimano HG500, 11x34
KETTING	KMC X10 with Missing Link
CRANKSET	FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA Mega EXO

WIELSET	
VELGEN	Giant S-X2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless
BANDEN	Giant CrossCut AT 2, 700x38c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 1.749,00

## GEOMETRIE

FRAME	S		M		ML		L		XL	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	450	470	490	510	530					
Zitbuis Hoek	73,5°	73,5°	73,0°	73,0°	73,0°					
Frame Lengte (horizontaal) (mm)	550	560	575	585	600					
Balhoofdbuis Lengte (mm)	135	150	165	180	195					
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°					
Vork Sprong (mm)	50	50	50	50	50					
Naloop (mm)	72   75	68   72	65   68	65   68	65   68					
Wielbasis (mm)	1025   1035	1030   1040	1035   1045	1045   1055	1061   1071					
Liggende achtervork lengte (mm)	430   440	430   440	430   440	430   440	430   440					
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81					
Stack (mm)	570	586	602	616	630					
Reach (mm)	381	387	391	397	407					
Stand Over Height (mm)	734   741	752   759	769   776	786   793	801   810					
Stuur breedte (mm)	420	440	440	460	460					
Stuurpen Lengte (mm)	60	70	80	80	90					
Cranklengte (mm)	170	172,5	172,5	175	175					
Wielmaat	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C					

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.