



## SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Asphalt Green
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact XR Ergo-Control, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	cork tape with gel
STUURPEN	Giant Sport, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELLEN	Giant D-Fuse, alloy, 14mm offset
ZADEL	Giant Approach
AFMONTAGE	
SHIFTERS	Shimano Sora, 2x9
VOORDERAILLEUR	Shimano Sora
ACHTERDERAILLEUR	Shimano Sora, long cage
REMMEN	Tektro MD-C550 mechanical, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano Sora
CASSETTE	Shimano HG400, 11x34
KETTING	KMC X9 with Missing Link
CRANKSET	FSA Vero Pro, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant S-X2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless
BANDEN	Giant CrossCut AT 2, 700x38c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

Adviesprijs: € 1.499,00

## GEOMETRIE

FRAME	S	M	ML	L	XL
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Zitbuis Lengte (mm)	450	470	490	510	530
Zitbuis Hoek	73,5°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	550	560	575	585	600
Balhoofdbuis Lengte (mm)	135	150	165	180	195
Balhoofdbuis Hoek	71,0°	71,5°	72,0°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	72   75	68   72	65   68	65   68	65   68
Wielbasis (mm)	1025   1035	1030   1040	1035   1045	1045   1055	1061   1071
Liggende achtervork lengte (mm)	430   440	430   440	430   440	430   440	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81	80   81
Stack (mm)	570	586	602	616	630
Reach (mm)	381	387	391	397	407
Stand Over Height (mm)	734   741	752   759	769   776	786   793	801   810
Stuur breedte (mm)	420	440	440	460	460
Stuurpen Lengte (mm)	60	70	80	80	90
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.