

REVOLT ADVANCED PRO 1

GIANT



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Meteor Storm
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout, down tube storage
VOORVORK	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
HANDVATTEN	Stratus Lite 3.0
STUURPEN	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
ZADELPEN	Giant D-Fuse SLR, composite, -5/+15mm offset
ZADEL	Giant Grit SL
AFMONTAGE	
SHIFTERS	SRAM Rival eTap AXS, 2x12
VOORDERAILLEUR	SRAM Rival eTap AXS
ACHTERDERAILLEUR	SRAM Rival eTap AXS
REMMEN	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
REMHENDELS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
KETTING	SRAM Rival D1
CRANKSET	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	CADEX GX, 700x40c, tubeless
EXTRA'S	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag

Adviesprijs: € 5.799,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Zitbuis Hoek	450	470	490	510	530
Frame Lengte (horizontaal) (mm)	73,5°	73,5°	73,0°	73,0°	73,0°
Balhoofdbuis Lengte (mm)	550	560	575	585	600
Balhoofdbuis Hoek	135	150	165	180	195
Vork Sprong (mm)	71,0°	71,5°	72,0°	72,0°	72,0°
Naloopt (mm)	50	50	50	50	50
Wielbasis (mm)	72 75	68 72	65 68	65 68	65 68
Liggende achtervork lengte (mm)	1020 1030	1026 1036	1031 1041	1041 1051	1056 1066
Bottom Bracket Drop (mm)	425 435	425 435	425 435	425 435	425 435
Stack (mm)	80 81	80 81	80 81	80 81	80 81
Reach (mm)	570	586	602	616	630
Stand Over Height (mm)	381	387	391	397	407
Stuur breedte (mm)	740 747	757 764	774 780	791 797	807 814
Stuurpen Lengte (mm)	420	440	440	460	460
Cranklengte (mm)	60	70	80	80	90
Wielmaat	170	172,5	172,5	175	175
	700c	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.